


GS12/50/250/CAR/M

GS12/100/250/CAR/M

1 Collettore di raffreddamento.

2 Doppia uscita.

3 Ruota pivotante.

24 ÷ 100

MODELLO Model	CODICE Code	Litri Liters		CFM	min-1	Cilindri Cylinders	Stadi Stages	bar	psi	kW	HP	Volt	Hz	dB/A	L x P x H cm	Kg
		Litri/min Liters/min	Litri/min Liters/min													
GS12/24/250/CAR/M	AF-004	24	250	8,8	1.250	2	+	10	145	1,5	2	230	50	73	80x35x69	41
GS12/50/250/CAR/M	AF-006	50	250	8,8	1.250	2	+	10	145	1,5	2	230	50	72	90x35x72	45
GS12/50/250/CAR/F	AF-007	50	250	8,8	1.250	2	+	10	145	1,5	2	400	50	72	90x35x72	45
GS12/100/250/CAR/M	AF-008	100	250	8,8	1.250	2	1	10	145	1,5	2	230	50	72	115x37x80	62
GS12/100/250/CAR/F	AF-009	100	250	8,8	1.250	2	+	10	145	1,5	2	400	50	72	115x37x80	62
GS17/100/320/CAR/M	AF-010	100	320	11,3	1.500	2	+	10	145	2,2	3	230	50	74	115x37x80	65
GS17/100/330/CAR/F	AF-011	100	330	11,6	1.550	2	+	10	145	2,2	3	400	50	74	115x37x80	65
GS25/100/380/CAR/M	AF-127	100	360	12,7	1.100	2	+	10	145	2,2	3	230	50	76	115x37x82	67
GS25/100/380/CAR/F	AF-128	100	360	12,7	1.100	2	+	10	145	2,2	3	400	50	76	115x37x82	67
GS25/100/500/CAR/F	AF-134	100	500	17,6	1.450	2	+	10	145	3	4	400	50	78	115x37x82	69